

**Series 2, Integrated cooker hood, 60 cm, Silver  
DEM63AC00B**



**Optional accessories**

DWZ0IM0A0 Standard odor filter (replacement)

**Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.**

- **LED Illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- **High extraction rate - for continuously clean air in the kitchen.**
- **Dishwasher safe metal grease filter**
- **3 Power Levels:** Adjust the extraction intensity according to your cooking needs.
- **Ducted or un-ducted options:** Flexibility to install our hoods in both ducted and un-ducted options.

**Technical Data**

Typology: .....	Built-in/Built-under
Length electrical supply cord: .....	150 cm
Height of the appliance: .....	402 mm
Minimum distance above an electric hob: .....	500 mm
Minimum distance above a gas hob: .....	650 mm
Net weight: .....	10.3 kg
Type of control: .....	Mechanical
Number of speed settings: .....	3
Max. air extraction: .....	368 m <sup>3</sup> /h
Max. air recirculation: .....	272 m <sup>3</sup> /h
Maximum Air flow: .....	368 m <sup>3</sup> /h
Number of lights: .....	2
Noise level: .....	62 dB(A) re 1pW
Diameter of air outlet: .....	150 / 120 mm
Grease filter material: .....	Washable aluminium
EAN code: .....	4242005041107
Connection rating: .....	126 W
Fuse protection: .....	10 A
Voltage: .....	220-240 V
Frequency: .....	50; 60 Hz
Plug type: .....	GB plug
Installation typology: .....	Wall-mounted



## **Series 2, Integrated cooker hood, 60 cm, Silver DEM63AC00B**

**Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.**

### **Key performance features:**

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 368 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB\*

### **Features**

- Push button control for extractor speeds and light
- 3 power levels
- Single motor
- 2 x 3W LED
- Colour Temperature: 2700 K
- 2 removable metal grease filter cassettes
- Installation: Between Cupboards

### **Design**

- Integrated hood
- Push button control
- Mechanical

### **Performance/technical information**

- Suitable for ducted or recirculating operation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 62 dB(A) re 1 pW
- Light Intensity: 188 lux
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 65.7 kWh/year\*

### **Optional accessories**

- Recirculating kit DWZ0IM0A0

\* In accordance with the EU-Regulation No 65/2014

**Series 2, Integrated cooker hood, 60  
cm, Silver  
DEM63AC00B**

