

**Series 2, Wall-mounted cooker hood,  
60 cm, Stainless steel  
DWP64CC50M**



**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

- Quiet extraction with powerful performance
- High extraction rate - for continuously clean air in the kitchen.
- Dishwasher safe metal grease filter
- **3 Power Levels:** Adjust the extraction intensity according to your cooking needs.
- Dishwasher safe aluminum mesh filters

**Optional accessories**

- DWA0KP6A Standard odor filter  
 DWZ6HP1U2 Standard recirculation kit

**Technical Data**

Color chimney: .....	Stainless steel
Typology: .....	Wall-mounted
Length electrical supply cord: .....	120 cm
Height of the chimney: .....	410-765/410-765 mm
Height of the appliance: .....	250 mm
Minimum distance above an electric hob: .....	650 mm
Minimum distance above a gas hob: .....	650 mm
Net weight: .....	9.2 kg
Type of control: .....	Mechanical
Number of speed settings: .....	3
Max. air extraction: .....	380 m <sup>3</sup> /h
Max. air recirculation: .....	235 m <sup>3</sup> /h
Maximum Air flow: .....	380 m <sup>3</sup> /h
Number of lights: .....	2
Noise level: .....	64 dB(A) re 1pW
Diameter of air outlet: .....	150 mm
Grease filter material: .....	Washable aluminium
EAN code: .....	4242002985299
Connection rating: .....	135 W
Voltage: .....	220-240 V
Frequency: .....	50 Hz
Plug type: .....	GB plug
Installation typology: .....	Wall-mounted



## Series 2, Wall-mounted cooker hood, 60 cm, Stainless steel DWP64CC50M

**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

### Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 380 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 64 dB dB\*

### Features

- 3 power levels
- 2 x LED 5W
- Colour Temperature: 4000 K
- 2 removable metal grease filter cassettes
- Installation: wall

### Design

- Chimney extractor hood
- Push button control
- Mechanical

### Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction charcoal filter (accessory) needed
- Maximum extraction rate exhaust air 380 m<sup>3</sup>/h according to EN 61591
- Extraction rate in recirculation mode:
  - Max. normal use: 235 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW
- Noise level in recirculation mode:
  - Max. normal use: 70 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
- Power rating: 135 W
- Light Intensity: 1000 lux
- Electrical cable length 1.2 m
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Dimensions exhaust air (HxWxD): 790-1015 x 598 x 470 mm
- Dimensions recirculating (HxWxD): 790-1015 x 598 x 470 mm
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 72.8 kWh/year\*

### Optional accessories

- Recirculating kit DWA0KP6A

\* In accordance with the EU-Regulation No 65/2014

**Series 2, Wall-mounted cooker hood,  
60 cm, Stainless steel  
DWP64CC50M**

