



Product Benefits & Features

- Control type: Push buttons with 3 speeds.
- Aluminium grease filters
- Charcoal filter: This charcoal filter is used in recirculation mode to remove cooking smells. Needs replacing periodically.
- Extraction mode
- Recirculation mode
- Grease filter type and number: Aluminium mesh, 2

Product Specification

Main Colour	Stainless Steel	Max Recirculated Extraction Rate (m ³ /h)	490
Number of Speed Settings	3	Min Recirculated Noise Level (dB)	63
Control Type	Mechanical push buttons	Max Recirculated Noise Level (dB)	72
Lamp Type	LED stripe	PNC	942 022 933
Energy Rating	B	Bar Code	7333394152219
Ducted Extraction Rate - Min/Max/Intensive (m ³ /h)	290/600/-	Net Weight (Kg)	12.8
Ducted Noise Level - Min/Max/Intensive (dB)	52/69/-	Gross Weight (Kg)	17.7
Grease Filter Efficiency Rating	C	Dimensions (mm) (HxWxD)	1180x598x460
Minimum Distance from Electric Hob (cm)	50	Installation Type	Chimney
Minimum Distance from Gas Hob (cm)	65	Number of Grease Filters	2
Annual Energy Consumption (kWh)	64.8	Grease Filter Type	Aluminium mesh
Size (cm)	60	Cord Length (m)	1.35
Extraction Type - Recirculation	Yes	Air Outlet (mm)	150
Extraction Type - Ducted	Yes	Voltage (V)	220-240
Light Temperature (k)	3000	Required Fuse (A)	N/A
Number of Lights	2	Charcoal Filter	Included
Hob2Hood Connection	No	Charcoal Filter Type	MCFB97
Fluid Dynamic Efficiency Rating	B	Long Life Filter Type	MCFB98
Lighting Efficiency Rating	A	Super Performing Filter Type	NO
Min Recirculated Extraction Rate (m ³ /h)	280	OdourClean Plus Carbon filter	Optional Accessory

