



High-performance odour removal

5000 ExtractionTech Plus ensures your kitchen air stays fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.

Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

Product Benefits & Features

ExtractionTech Plus: High-performance odour removal



ExtractionTech Plus keeps your kitchen smelling fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.

Spotlight the details with the Pure Illumination



Energy-efficient Pure Illumination provides full visibility while cooking. The LED lights illuminate the entire cooking surface, making it easy to see every detail of your meal preparation.

Reliable, easy-to-clean grease filter keeps kitchen fresh



Convenient, reliable grease filter ensures your kitchen stays fresh and hood performs at its best. Wash by hand or in dishwasher.

- Control type: Push buttons with 3 speeds.
- Aluminium grease filters
- Charcoal filter: This charcoal filter is used in recirculation mode to remove cooking smells. Needs replacing periodically.
- Extraction mode
- Recirculation mode
- Grease filter type and number: Aluminium mesh, 2

Product Specification

Main Colour	Stainless Steel	Max Recirculated Extraction Rate (m ³ /h)	400
Number of Speed Settings	3	Min Recirculated Noise Level (dB)	66
Control Type	Mechanical push buttons	Max Recirculated Noise Level (dB)	75
Lamp Type	LED spotlight	PNC	942 150 810
Energy Rating	B	Bar Code	7332543619146
Ducted Extraction Rate - Min/Max/Intensive (m ³ /h)	240/603/-	Net weight (kg)	15.5
Ducted Noise Level - Min/Max/Intensive (dB)	46/69/-	Gross weight (kg)	20.2
Grease Filter Efficiency Rating	C	Dimensions (mm) (HxWxD)	1090x898x500
Minimum Distance from Electric Hob (cm)	50	Installation Type	Chimney
Minimum Distance from Gas Hob (cm)	65	Number of Grease Filters	2
Annual Energy Consumption (kWh)	56.4	Grease Filter Type	Aluminium mesh
Size (cm)	90	Cord Length (m)	1.5
Extraction Type - Recirculation	Yes	Air Outlet (mm)	150
Extraction Type - Ducted (External)	Yes	Charcoal Filter	Included
Light temperature, K	3000	Charcoal Filter Type	MCFE01ST
Number of Lights	2	Long Life Filter Type	MCFE11PL
Hob2Hood Connection	No	Super Performing Filter Type	SUPCHARE22
Fluid Dynamic Efficiency Rating	B	OdourClean Plus Carbon filter	Optional accessory
Lighting Efficiency Rating	A	OdourClean Pro Carbon filter	Optional accessory
Min Recirculated Extraction Rate (m ³ /h)	224		

