



The perfect partner when you cook

The 6000 Hob2Hood® Cooker Hood wirelessly connects to the hob. The lights activate when you turn on the hob, and the fan speed is regulated based on the heat setting on the hob. Experience an odour-free kitchen every time you cook.

Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

Product Benefits & Features

Hob2Hood®. The perfect partner when you cook.

The Hob2Hood® function wirelessly activates the hood lights when you turn on the hob. When you start cooking, the fan speed is regulated based on the heat settings on the hob. Cook delicious meals without worrying about odours and vapours.



ExtractionTech Plus: High-performance odour removal

ExtractionTech Plus keeps your kitchen smelling fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.



Spotlight the details with the Pure Illumination

Energy-efficient Pure Illumination provides full visibility while cooking. The LED lights illuminate the entire cooking surface, making it easy to see every detail of your meal preparation.




Reliable, easy-to-clean grease filter keeps kitchen fresh

Convenient, reliable grease filter ensures your kitchen stays fresh and hood performs at its best. Wash by hand or in dishwasher.



Filter cleaning notification system

The hood has a convenient filter cleaning notification system. An indicator on the hood alerts you when the grease filter and carbon filter need cleaning – there's no need to keep track of it yourself.



- Control type: Electronic touch controls with 3+Intensive; Breeze function speeds.
- Charcoal filter: This charcoal filter is used in recirculation mode to remove cooking smells. Needs replacing periodically.
- Extraction mode
- Recirculation mode
- Hob2Hood®: Allows you to control the cooker hood via your hob.
- Grease filter indicator.
- Charcoal filter indicator.
- Grease filter type and number: Stainless steel design filter, 1

Product Specification

Main Colour	Stainless Steel	Max Recirculated Extraction Rate (m ³ /h)	302
Number of Speed Settings	3+Intensive; Breeze function	Intensive Recirculated Extraction Rate (m ³ /h)	524
Control Type	Touch on glass	Min Recirculated Noise Level (dB)	44
Lamp Type	LED spotlight	Max Recirculated Noise Level (dB)	62
Energy Rating	A	PNC	942 150 587
Ducted Extraction Rate - Min/Max/Intensive (m ³ /h)	175/352/779	Bar Code	7332543538188
Ducted Noise Level - Min/Max/Intensive (dB)	38/55/73	Net weight (kg)	15.1
Grease Filter Efficiency Rating	C	Gross weight (kg)	19
Minimum Distance from Electric Hob (cm)	50	Dimensions (mm) (HxWxD)	1175x598x500
Minimum Distance from Gas Hob (cm)	65	Installation Type	Chimney
Annual Energy Consumption (kWh)	57.7	Number of Grease Filters	1
Size (cm)	60	Grease Filter Type	Stainless steel design filter
Extraction Type - Recirculation	Yes	Cord Length (m)	1.5
Extraction Type - Ducted (External)	Yes	Air Outlet (mm)	150
Light temperature, K	3000	Recommended fuse (A)	4
Number of Lights	2	Charcoal Filter	Included
Hob2Hood Connection	Yes	Charcoal Filter Type	MCFE01ST
Fluid Dynamic Efficiency Rating	A	Long Life Filter Type	MCFE11PL
Lighting Efficiency Rating	A	Super Performing Filter Type	SUPCHARE22
Min Recirculated Extraction Rate (m ³ /h)	127	OdourClean Plus Carbon filter	Not available

