



The perfect partner when you cook

The 6000 Hob2Hood® Cooker Hood wirelessly connects to the hob. The lights activate when you turn on the hob, and the fan speed is regulated based on the heat setting on the hob. Experience an odour-free kitchen every time you cook.

Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

Product Benefits & Features

Natural air, effortlessly and silently.

The sleekly designed AEG hood removes lingering odours quietly thanks to a super quiet breeze technology. So you can have a better environment in your kitchen effortlessly and silently.



The hands-free hood

This cooker hood has Hob2Hood®, a useful feature that automatically controls your cooker hood and lights. Leave Hob2Hood® to regulate the fan while you concentrate on the key moments involved in getting your dish just right. But if you'd rather adjust the fan speed yourself,



Clean air with less energy

A strong motor with low-energy consumption means this hood is reliable and efficiently clears away kitchen odours.

Clean air. Designed to last

This filter captures and cleans away cooking smells incredibly efficiently to leave kitchens fresh. The longest-lasting disposable filter, it can be washed and reactivated to ensure it maintains its high odour-filtering performance.

All cooking vapours removed – in silence

Thanks to innovative technology, this hood clears your kitchen of unwanted cooking vapours almost unnoticeably. What's more, the cooker hood's virtually silent operation helps you create the perfect atmosphere in your home.



- Control type: Electronic touch controls with 3+Intensive; Breeze function speeds.
- Charcoal filter: This charcoal filter is used in recirculation mode to remove cooking smells. Needs replacing periodically.
- Extraction mode
- Recirculation mode
- Hob2Hood®: Allows you to control the cooker hood via your hob.
- Grease filter indicator.
- Charcoal filter indicator.
- Grease filter type and number: Stainless steel design filter, 2

Product Specification

Main Colour	Stainless Steel	Max Recirculated Extraction Rate (m ³ /h)	302
Number of Speed Settings	3+Intensive; Breeze function	Intensive Recirculated Extraction Rate (m ³ /h)	524
Control Type	Touch on glass	Min Recirculated Noise Level (dB)	44
Lamp Type	LED spotlight	Max Recirculated Noise Level (dB)	62
Energy Rating	A	PNC	942 150 585
Ducted Extraction Rate - Min/Max/Intensive (m ³ /h)	175/352/779	Bar Code	7332543538164
Ducted Noise Level - Min/Max/Intensive (dB)	38/55/73	Net weight (kg)	16.6
Grease Filter Efficiency Rating	C	Gross weight (kg)	21.3
Minimum Distance from Electric Hob (cm)	50	Dimensions (mm) (HxWxD)	1175x898x500
Minimum Distance from Gas Hob (cm)	65	Installation Type	Chimney
Annual Energy Consumption (kWh)	57.7	Number of Grease Filters	2
Size (cm)	90	Grease Filter Type	Stainless steel design filter
Extraction Type - Recirculation	Yes	Cord Length (m)	1.5
Extraction Type - Ducted (External)	Yes	Air Outlet (mm)	150
Light temperature, K	3000	Recommended fuse (A)	4
Number of Lights	2	Charcoal Filter	Included
Hob2Hood Connection	Yes	Charcoal Filter Type	MCFE01ST
Fluid Dynamic Efficiency Rating	A	Long Life Filter Type	MCFE11PL
Lighting Efficiency Rating	A	Super Performing Filter Type	SUPCHARE22
Min Recirculated Extraction Rate (m ³ /h)	127	OdourClean Plus Carbon filter	Not available

