



### The perfect partner when you cook

The 6000 Hob2Hood® Cooker Hood wirelessly connects to the hob. The lights activate when you turn on the hob, and the fan speed is regulated based on the heat setting on the hob. Experience an odour-free kitchen every time you cook.

## Product Benefits & Features

### Hob2Hood®. The perfect partner when you cook.

The Hob2Hood® function wirelessly activates the hood lights when you turn on the hob. When you start cooking, the fan speed is regulated based on the heat settings on the hob. Cook delicious meals without worrying about odours and vapours.



### Natural air, effortlessly and silently with the Breeze function

The Breeze function refreshes your kitchen air after cooking while quietly extracting lingering kitchen odours. Eat, relax and entertain in an enjoyable kitchen atmosphere, effortlessly and silently.



### ExtractionTech Pro cooker hood: High power, exceptional freshness

Experience superior kitchen air quality with the ExtractionTech Pro cooker hood. Equipped with our most powerful motor and intensive speed option, it efficiently extracts cooking vapours ensuring an exceptionally fresh cooking environment.

### Spotlight the details with the Pure Illumination

Energy-efficient Pure Illumination provides full visibility while cooking. The LED lights illuminate the entire cooking surface, making it easy to see every detail of your meal preparation.



### Reliable, easy-to-clean grease filter keeps kitchen fresh

Convenient, reliable grease filter ensures your kitchen stays fresh and hood performs at its best. Wash by hand or in dishwasher.



- Control type: Electronic touch controls with 3+Intensive; Breeze function speeds.
- Aluminium grease filters
- Charcoal filter: This charcoal filter is used in recirculation mode to remove cooking smells. Needs replacing periodically.
- Extraction mode
- Recirculation mode
- Hob2Hood®: Allows you to control the cooker hood via your hob.
- Grease filter indicator.
- Charcoal filter indicator.
- Grease filter type and number: Aluminium mesh, 3

#### Product Specification

Main Colour	Stainless Steel	Max Recirculated Extraction Rate (m <sup>3</sup> /h)	535
Number of Speed Settings	3+Intensive; Breeze function	Intensive Recirculated Extraction Rate (m <sup>3</sup> /h)	565
Control Type	Touch on glass	Min Recirculated Noise Level (dB)	67
Lamp Type	LED stripe	Max Recirculated Noise Level (dB)	74
Energy Rating	A+	PNC	942 022 932
Ducted Extraction Rate - Min/Max/Intensive (m <sup>3</sup> /h)	320/610/730	Bar Code	7333394152233
Ducted Noise Level - Min/Max/Intensive (dB)	56/70/74	Net Weight (Kg)	15.1
Grease Filter Efficiency Rating	C	Gross Weight (Kg)	20.2
Minimum Distance from Electric Hob (cm)	50	Dimensions (mm) (HxWxD)	1180x898x460
Minimum Distance from Gas Hob (cm)	65	Installation Type	Chimney
Annual Energy Consumption (kWh)	43.7	Number of Grease Filters	3
Size (cm)	90	Grease Filter Type	Aluminium mesh
Extraction Type - Recirculation	Yes	Cord Length (m)	1.35
Extraction Type - Ducted	Yes	Air Outlet (mm)	150
Light Temperature (k)	3000	Voltage (V)	220-240
Number of Lights	1	Required Fuse (A)	N/A
Hob2Hood Connection	Yes	Charcoal Filter	Included
Fluid Dynamic Efficiency Rating	A	Charcoal Filter Type	MCFB97
Lighting Efficiency Rating	A	Long Life Filter Type	MCFB98
Min Recirculated Extraction Rate (m <sup>3</sup> /h)	340	Super Performing Filter Type	NO

