



High-performance odour removal

5000 ExtractionTech Plus ensures your kitchen air stays fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.

Product Benefits & Features

ExtractionTech Plus: High-performance odour removal



ExtractionTech Plus keeps your kitchen smelling fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.

Spotlight the details with the Pure Illumination



Energy-efficient Pure Illumination provides full visibility while cooking. The LED lights illuminate the entire cooking surface, making it easy to see every detail of your meal preparation.

Reliable, easy-to-clean grease filter keeps kitchen fresh



Convenient, reliable grease filter ensures your kitchen stays fresh and hood performs at its best. Wash by hand or in dishwasher.

- Control type: Push buttons with 3+Intensive speeds.
- Aluminium grease filters
- Charcoal filter: This charcoal filter is used in recirculation mode to remove cooking smells. Needs replacing periodically.
- Recirculation mode
- Grease filter indicator.
- Charcoal filter indicator.
- Grease filter type and number: Aluminium mesh, 1
- Remote control included

Product Specification

Main Colour	Black	Intensive Recirculated Extraction Rate (m ³ /h)	350
Number of Speed Settings	3+Intensive	Min Recirculated Noise Level (dB)	43
Control Type	Electronic push buttons	Max Recirculated Noise Level (dB)	70
Lamp Type	LED spotlight	PNC	942 051 290
Energy Rating	No	Bar Code	7332543702893
Ducted Extraction Rate - Min/Max/Intensive (m ³ /h)	-/-/-	Net weight (kg)	12.1
Ducted Noise Level - Min/Max/Intensive (dB)	-/-/-	Gross weight (kg)	18.1
Grease Filter Efficiency Rating	No	Dimensions (mm) (HxWxD)	1250x500x500
Minimum Distance from Electric Hob (cm)	50	Installation Type	Island
Minimum Distance from Gas Hob (cm)	65	Number of Grease Filters	1
Size (cm)	50	Grease Filter Type	Aluminium mesh
Extraction Type - Recirculation	Yes	Cord Length (m)	1.56
Extraction Type - Ducted (External)	No	Voltage (V)	220-240
Light temperature, K	3000	Recommended fuse (A)	N/A
Number of Lights	3	Charcoal Filter	Included
Hob2Hood Connection	No	Charcoal Filter Type	MCFB29
Fluid Dynamic Efficiency Rating	No	Long Life Filter Type	No
Lighting Efficiency Rating	No	Super Performing Filter Type	NO
Min Recirculated Extraction Rate (m ³ /h)	260	OdourClean Pro Carbon filter	Not available
Max Recirculated Extraction Rate (m ³ /h)	330		

