



The perfect partner when you cook

The 6000 Hob2Hood® Cooker Hood wirelessly connects to the hob. The lights activate when you turn on the hob, and the fan speed is regulated based on the heat setting on the hob. Experience an odour-free kitchen every time you cook.

Product Benefits & Features

Hob2Hood®. The perfect partner when you cook.

The Hob2Hood® function wirelessly activates the hood lights when you turn on the hob. When you start cooking, the fan speed is regulated based on the heat settings on the hob. Cook delicious meals without worrying about odours and vapours.



ExtractionTech Pro cooker hood: High power, exceptional freshness

Experience superior kitchen air quality with the ExtractionTech Pro cooker hood. Equipped with our most powerful motor and intensive speed option, it efficiently extracts cooking vapours ensuring an exceptionally fresh cooking environment.



Spotlight the details with the Pure Illumination

Energy-efficient Pure Illumination provides full visibility while cooking. The LED lights illuminate the entire cooking surface, making it easy to see every detail of your meal preparation.



High-performance grease removal with the Grease Filter Plus

The Grease Filter Plus delivers high-performance removal of grease, ensuring a clean cooking environment. Easy to clean by hand or in the dishwasher, the filter consistently maintains optimal efficiency for superior results.



Filter cleaning notification system

The hood has a convenient filter cleaning notification system. An indicator on the hood alerts you when the grease filter and carbon filter need cleaning – there's no need to keep track of it yourself.



- Control type: Electronic touch controls with 3+Intensive;Breeze function speeds.
- Aluminium grease filters
- Charcoal filter: This charcoal filter is used in recirculation mode to remove cooking smells. Needs replacing periodically.
- Extraction mode
- Recirculation mode
- Hob2Hood®: Allows you to control the cooker hood via your hob.
- Grease filter indicator.
- Charcoal filter indicator.
- Grease filter type and number: Black Aluminium mesh, 3

Product Specification

Main Colour	Black	Max Recirculated Extraction Rate (m ³ /h)	515
Number of Speed Settings	3+Intensive;Breeze function	Intensive Recirculated Extraction Rate (m ³ /h)	545
Control Type	Touch on glass, White & red backlight	Min Recirculated Noise Level (dB)	66
Lamp Type	LED stripe	Max Recirculated Noise Level (dB)	75
Energy Rating	A	PNC	942 022 937
Ducted Extraction Rate - Min/Max/Intensive (m ³ /h)	295/600/730	Bar Code	7333394152806
Ducted Noise Level - Min/Max/Intensive (dB)	56/70/74	Net weight (kg)	15.9
Grease Filter Efficiency Rating	C	Gross weight (kg)	21.1
Minimum Distance from Electric Hob (cm)	50	Dimensions (mm) (HxWxD)	1180x898x454
Minimum Distance from Gas Hob (cm)	65	Installation Type	Chimney
Annual Energy Consumption (kWh)	62.5	Number of Grease Filters	3
Size (cm)	90	Grease Filter Type	Black Aluminium mesh
Extraction Type - Recirculation	Yes	Cord Length (m)	1.35
Extraction Type - Ducted (External)	Yes	Air Outlet (mm)	150
Light temperature, K	3000	Voltage (V)	220-240
Number of Lights	1	Recommended fuse (A)	N/A
Hob2Hood Connection	Yes	Charcoal Filter	Included
Fluid Dynamic Efficiency Rating	A	Charcoal Filter Type	MCFB97
Lighting Efficiency Rating	A	Long Life Filter Type	MCFB98
Min Recirculated Extraction Rate (m ³ /h)	275	Super Performing Filter Type	NO

