



**The perfect partner when you cook**

The 6000 Hob2Hood® Cooker Hood wirelessly connects to the hob. The lights activate when you turn on the hob, and the fan speed is regulated based on the heat setting on the hob. Experience an odour-free kitchen every time you cook.

**Product Benefits & Features**

**Hob2Hood®. The perfect partner when you cook.**

The Hob2Hood® function wirelessly activates the hood lights when you turn on the hob. When you start cooking, the fan speed is regulated based on the heat settings on the hob. Cook delicious meals without worrying about odours and vapours.



**High Performance Motor. Always fresh kitchen air**

Elevate your kitchen atmosphere with the High Performance Motor. Its powerful engine swiftly eliminates cooking odours, leaving your kitchen smelling fresh and clean.



**Filter cleaning notification system**

The hood has a convenient filter cleaning notification system. An indicator on the hood alerts you when the grease filter and carbon filter need cleaning – there's no need to keep track of it yourself.



**LED Strip – put your cooking in the best light**

Illuminate your culinary space with long-lasting LED Strip lighting. Benefit from improved visibility and ambient lighting when cooking your favourite dish with efficient lighting.



**Quick and reliable PerfectFit Installation**

For fast & accurate PerfectFit Installation of your new cooker hood. It's our Best-In-Class Installation with fewer mounting steps compared to previous models, it provides a user-friendly experience, making the work an easy one-person job fitting in all standard niches.



- Control type: Electronic touch controls with 3+Intensive speeds.
- Extraction mode
- Recirculation mode
- Hob2Hood®: Allows you to control the cooker hood via your hob.
- Grease filter indicator.
- Charcoal filter indicator.
- Grease filter type and number: Stainless steel design filter, 1

## Product Specification

|  |                 |  |                               |
|--|-----------------|--|-------------------------------|
| Main Colour  | Stainless Steel | Max Recirculated Extraction Rate (m <sup>3</sup> /h)       | 440                           |
| Number of Speed Settings                                       | 3+Intensive     | Intensive Recirculated Extraction Rate (m <sup>3</sup> /h) | 590                           |
| Control Type   | Touch on glass  | Min Recirculated Noise Level (dB)                          | 54                            |
| Lamp Type  | LED stripe      | Max Recirculated Noise Level (dB)                          | 69                            |
| Energy Rating  | A               | PNC  | 942 051 501                   |
| Ducted Extraction Rate - Min/Max/Intensive (m <sup>3</sup> /h) | 260/445/750     | Bar Code   | 7333394048888                 |
| Ducted Noise Level - Min/Max/Intensive (dB)                    | 45/57/70        | Net Weight (Kg)  | 13.14                         |
| Grease Filter Efficiency Rating                                | B               | Gross Weight (Kg)  | 18.6                          |
| Minimum Distance from Electric Hob (cm)                        | 50              | Dimensions (mm) (HxWxD)                                    | 330x1200x308                  |
| Minimum Distance from Gas Hob (cm)                             | 65              | Installation Type  | Integrated                    |
| Annual Energy Consumption (kWh)                                | 45              | Number of Grease Filters                                   | 1                             |
| Size (cm)  | 120             | Grease Filter Type   | Stainless steel design filter |
| Extraction Type - Recirculation                                | Yes             | Cord Length (m)  | 1.4                           |
| Extraction Type - Ducted                                       | Yes             | Air Outlet (mm)  | 150                           |
| Light Temperature (k)  | 3000            | Voltage (V)  | 220-240                       |
| Number of Lights   | 1               | Required Fuse (A)  | N/A                           |
| Hob2Hood Connection  | Yes             | Charcoal Filter  | Not available                 |
| Fluid Dynamic Efficiency Rating                                | A               | Charcoal Filter Type                                       | NO                            |
| Lighting Efficiency Rating                                     | A               | Long Life Filter Type                                      | MCFB86PL                      |
| Min Recirculated Extraction Rate (m <sup>3</sup> /h)           | 225             | Super Performing Filter Type                               | NO                            |