


N 70, GAS HOB, 60 CM, STAINLESS STEEL
T26CIH8N0



Optional accessories

Z1365WX0	Wireless food thermometer
Z2471X0	Wok ring
Z9404SE0	4 pieces Set
Z9406SE0	6 pieces Set

The gas hob with precise flame control, removable dials and pan supports that are suitable for dishwashers - for Comfort Clean.

- ✓ FlameSelect®: Gain precise control of your flame.
- ✓ Metallic Sword Dial: Precise and removable for easy cleaning.
- ✓ Cast Iron Pan Supports: For maximum stability and dishwasher cleaning.
- ✓ Wok Burner: Powerful cooking at up to 3.5 kW.
- ✓ Gas Safety Cut-Off: Safety first! No flame, no gas flow.

Features

Technical Data

Product name/family:gas hob w
integrated controls
Built-in / Free-standing: Built-in
Energy input: Gas
Number of cooking zones: 4
Required niche size for installation (HxWxD): 45 x 560-560 x
480-490 mm
Width of the appliance: 582 mm
Dimensions: 45x582x520 mm
Dimensions of the packed product (HxWxD): 141x651x578 mm
Net weight: 10.8 kg
Gross weight: 12.0 kg
Residual heat indicator: Without
Location of control panel: Front
Basic surface material: Stainless steel
Color of surface: Stainless steel
Length electrical supply cord: 100 cm
EAN code: 4242004284536
Gas connection rating: 8000 W
Fuse protection: 3 A
Voltage: 220-240 V
Frequency: 50; 60 Hz



N 70, GAS HOB, 60 CM, STAINLESS STEEL T26CIH8N0

Features

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet
- full metal

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner hob
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: WOK burner up to 3.5 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU)
- Natural gas L 25 mbar (NL)
- Liquid gas G30,31 28-30/37mbar
- Liquid gas G30 37 mbar (PL)
- Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.5 x 582 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 490)
- Min. worktop thickness: 20 mm
- Power cord: 1 m
- Connected load: 8 KW

N 70, GAS HOB, 60 CM, STAINLESS STEEL
T26CIH8N0

Dimensioned drawings

